

e3 Specifications - 3 Models

Model	e3-3.2 Si	e3-3.6 Sii	e3-6.0 Sii
Motor Type	2x QS Type 171 8kW electric motors	2x QS Type 171 8kW electric motors	2x QS Type 171 8kW electric motors
Peak Torque	71Nm/motor	80Nm/motor	80Nm/motor
Continuous Torque	37Nm/motor 380Nm at wheels	41Nm/motor 440Nm at wheels	41Nm/motor 440Nm at wheels
Drive System	16mm commercial grade chain drive – 5:1 reduction	16mm commercial grade chain drive – 6:3:1 reduction	16mm commercial grade chain drive – 6:3:1 reduction
Front / Rear Tyres	22 x 8 - 11 / 22 x 12 - 10	22 x 8 - 11 / 25 x 12 - 10	22 x 8 - 11 / 25 x 12 - 10
Brakes	Regenerative braking combined with dual rear hydraulic disk brakes	Regenerative braking combined with dual rear hydraulic disk brakes	Regenerative braking combined with dual rear hydraulic disk brakes
Speed Governed	15 - 45 kilometres per hour	15 - 50 kilometres per hour	15 - 50 kilometres per hour
Turning Radius	3.6 metres	3.6 metres	3.6 metres
Load Capacity	380kg occupants and cargo	450kg occupants and cargo	450kg occupants and cargo
Tip Tray Size/Capacity	1.5m x 0.7m (1m2) 200kg Dumper Tray	1.5m x 0.7m (1m2) 250kg Tailgate Tray	1.5m x 0.7m (1m2) 200kg Tailgate Tray
Suspension	Rear-torsional	Front -spring & dampener Rear-torsional & dampener	Front -spring & dampener Rear-torsional & dampener
Battery Type	54v 60Ah Lithium (LFP)	60v 60Ah Lithium (LFP)	60v 100Ah Lithium (LFP)
Battery Capacity	3.2 kWh	3.6 kWh	6.0 kWh
Approximate Range Between Charges*	20-24km	27-30km	45-50km
Charge Time/Cycles	4hrs/6000	6hrs/6000	8.5hrs/6000
Dimensions	2.65m long x 1.5m wide	2.65m long x 1.5m wide	2.65m long x 1.5m wide
Ground Clearance	340mm	340mm	340mm
Seat Height	660mm	660mm	660mm
Curb Mass	366kg	379kg	392kg
Safety	Roll bar & inertia lap belts	Roll bar & inertia lap belts	Roll bar & inertia lap belts
Supplied With	Head light, tail lights, battery monitor, horn, charging lead, tow bar & ball, 2 x 12v outlets. *Range can be affected by a variety of conditions including speed, terrain, weight carried/towed & tyre pressure.	Head light, tail lights, battery monitor, horn, charging lead, tow bar & ball, 2 x 12v outlets. Bluetooth configuration connectivity, tools and toolbox.	Head light, tail lights, battery monitor, horn, charging lead, tow bar & ball, 2 x 12v outlets. Bluetooth configuration connectivity, tools and toolbox, roll bar spotlights, carry box and dual USB charging points.

Options & Accessories

- 40kg capacity Front Carry Rack
- Dewalt DS300 Tough Box with carry rack fitting clamps
- Roll bar Spotlights
- Full ROPS & Canopy Top with Windscreen & Wiper options
- Tip Tray - Dumper or Tailgated options
- Low Canopy Roll Bar

Specifications are subject to change and should be confirmed at time of order.



switchglobal.com